



# SLIDING SYSTEM NON INSULATED

COMFORT M9200 is a non-insulated sliding system with curved shape.

- Sash width 38 mm.
- Supports single or double glazing up to 20 mm thickness and sash weight up to 120 Kg.
- Suitable for any typology of sliding doors and windows, combined also with sliding shutters or/and fly screens.
- Two points locking hardware for a higher security level.





# /lum/l



## **TECHNICAL CHARACTERISTICS**

Visible aluminium face width	102 mm
Frame height	30 mm
Frame width	84/91,5 mm
Sash height	82,3 mm
Sash width	38 mm
Interlocking profile width	82,3 mm
Sash weight	up to 120 Kg
Glazing	4 - 20 mm

### **TYPOLOGIES**



Double horizontal sliding sash



Double horizontal sliding sash with fly-screen



Three horizontal sliding sashes



Single sliding sash into wall with fly-screen & shutter



Four horizontal sliding sashes with meeting stile



Double sliding sash into wall with meeting stile, fly-screen & shutter

### CERTIFICATES

Z	Air permeability EN 1026, EN12207	CLASS 3
53	Watertightness EN 1027, EN 12208	CLASS 1B
	Resistance to wind load EN 12210, EN 12211	CLASS B3

ALUMIL SA KILKIS INDUSTRIAL AREA GR 61 100, KILKIS TEL: +30 23410 79300 FAX: +30 23410 71988 www.alumil.com